

# Ricochet™ Flexible Wall Protection

## Strata - 21 Colorways

### PHYSICAL PROPERTIES

Width	Trim to 48"
Packaging	15-yd rolls
Thickness	0.032
Backing	Heavy Polyester/ Cotton knit
Repeat	N/A
Installation	Straight hang, Random match
Fire Safety	Class "A" rated ASTM E-84; NFPA 286

### ENVIRONMENTAL & HEALTH

Indoor Air	Meets California Section 01350
Fungal Resistant	ASTM G-21
Bacterial Resistant	ASTM G-22
HPD	third-party classified
EPD	third-party classified
NSF/ANSI 342	third-party certified, ask distributor

### CHEMICAL

Chemical Resistance ASTM D-1308, Spot test covered 3.1.1
<b>Cleaning Agents</b>
Tide w/H2O
Virex
Ammonia
Isopropyl Alcohol
Goof Off
Fantastik
Lysol
Hydrogen Peroxide
Bleach
Methyl Ethyl Ketone
Results: No change in Ricochet surface from exposure to these agents.

### CLEANING

Cleaning ASTM F-793, SECTION 7.5
<b>Staining Agents</b>
Grape Juice
Mustard
Black Sharpie
Ink Pen
Betadine
Shoe Polish
Lipstick
Black Rubber
Brake Fluid
Spray Paint
Results: Each staining agent above was wiped clean with at least one listed cleaning agent.

### ABRASION

Abrasion Resistance ASTM D- 4060-14, Taber Method
<b>Test Spec</b>
CS-10F wheel, 500 gram load @200 cycles
Weight loss: 0.02%

### IMPACT

Impact Resistance ASTM D-5420-10, Gardner Method	
<b>Pattern</b>	<b>In-Lbs</b>
Strata	100+

Best stain removal results can be achieved by use of progressively strong, non-abrasive cleaners, and which can be supplemented by use of a soft bristle brush.

### OTHER

5 year warranty against manufacturing defects.

Accessories: Coordinating corner guards, top trim and Type II wallcovering (on selected colorways) available. Installs with techniques similar to Type II vinyl wallcovering, including seaming with overlap and double-cut process. See full Installation Instructions. Sold in 15-yd coreless rolls, one per shipping box (approximately 42 lbs)

IPC.3149/REV.1